808 Silicone Spray

CRC Industries (CRC Industries New Zealand)

Chemwatch Hazard Alert Code: **3**

Chemwatch: **5617-10**
Version No: **2.1**
Safety Data Sheet according to the Health and Safety at Work (Hazardous Substances) Regulations 2017

Initial Date: **05/07/2023**
Revision Date: **05/07/2023**
Print Date: **05/10/2026**
S.GHS.NZL.EN

SECTION 1 Identification of the substance / mixture and of the company / undertaking

Product Identifier

Product name	808 Silicone Spray
Chemical Name	Not Applicable
Synonyms	3055, 1010282 - 808 Silicone Spray 500ml; 3050, 1011751 - 808 Silicone Permastraw 380ml; 1752483 - Race Series 808 , Silicone 400g; 1010281 - 808 Silicone 80ml
Proper shipping name	AEROSOLS
Chemical formula	Not Applicable
Other means of identification	Not Available

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	Silicone lubricant, Application is by spray atomisation from a hand held aerosol pack. Use according to manufacturer's directions.

Details of the manufacturer or importer of the safety data sheet

Registered company name	**CRC Industries (CRC Industries New Zealand)**
Address	10 Highbrook Drive East Tamaki Auckland New Zealand
Telephone	+64 9 272 2700
Fax	+64 9 274 9696
Website	www.crc.co.nz
Email	- No EMAL ID NEEDED for NZ - JACK

Emergency telephone number

Association / Organisation	**CRC Industries (CRC Industries New Zealand)**	**CHEMWATCH EMERGENCY RESPONSE (24/7)**
Emergency telephone number(s)	NZ Poisons Centre 0800 POISON (0800 764 766)	+64 800 700 112 (ID#: 5617-10)
Other emergency telephone number(s)	111 (NZ Emergency Services)	+61 3 9573 3188

SECTION 2 Hazards identification

Classification of the substance or mixture

Classification [1]	Aerosols, Hazard Category 1, Skin Corrosion/Irritation Category 2, Specific Target Organ Toxicity - Single Exposure (Narcotic Effects) Category 3, Hazardous to the Aquatic Environment Long-Term Hazard Category 2
Legend:	***1. Classified by Chemwatch; 2. Classification drawn from CCID EPA NZ; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI***
Determined by Chemwatch using GHS/HSNO criteria	2.1.2A, 6.3A, 6.9B (narcotic effects), 9.1B

Label elements

Hazard pictogram(s)	

Signal word	**Danger**

Hazard statement(s)

H222+H229	Extremely flammable aerosol. Pressurized container: may burst if heated.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.

Precautionary statement(s) Prevention

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P271	Use only outdoors or in a well-ventilated area.

Precautionary statement(s) Response

P312	Call a POISON CENTER/doctor/physician/first aider/if you feel unwell.
P391	Collect spillage.
P302+P352	IF ON SKIN: Wash with plenty of water and soap.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Precautionary statement(s) Storage

P405	Store locked up.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.

Precautionary statement(s) Disposal

P501	Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.

No further product hazard information.

SECTION 3 Composition / information on ingredients

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name
64742-49-0.	10-30	naphtha petroleum, light, hydrotreated
63148-62-9	1-20	polydimethylsiloxane
68476-85-7.	30-60	hydrocarbon propellant

Legend:	***1. Classified by Chemwatch; 2. Classification drawn from CCID EPA NZ; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI; 4. Classification drawn from C&L; * EU IOELVs available***

SECTION 4 First aid measures

Description of first aid measures

Eye Contact	If aerosols come in contact with the eyes: ‣ Immediately hold the eyelids apart and flush the eye continuously for at least 15 minutes with fresh running water. ‣ Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. ‣ Transport to hospital or doctor without delay. ‣ Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	If solids or aerosol mists are deposited upon the skin:

	‣ Flush skin and hair with running water (and soap if available). ‣ Remove any adhering solids with industrial skin cleansing cream. ‣ **DO NOT** use solvents. ‣ Seek medical attention in the event of irritation.
Inhalation	If aerosols, fumes or combustion products are inhaled: ‣ Remove to fresh air. ‣ Lay patient down. Keep warm and rested. ‣ Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures. ‣ If breathing is shallow or has stopped, ensure clear airway and apply resuscitation, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary. ‣ Transport to hospital, or doctor.
Ingestion	‣ If swallowed do **NOT** induce vomiting. ‣ If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration. ‣ Observe the patient carefully. ‣ Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious. ‣ Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink. ‣ Seek medical advice.

Indication of any immediate medical attention and special treatment needed

For petroleum distillates
· In case of ingestion, gastric lavage with activated charcoal can be used promptly to prevent absorption - decontamination (induced emesis or lavage) is controversial and should be considered on the merits of each individual case; of course the usual precautions of an endotracheal tube should be considered prior to lavage, to prevent aspiration.
· Individuals intoxicated by petroleum distillates should be hospitalized immediately, with acute and continuing attention to neurologic and cardiopulmonary function.
· Positive pressure ventilation may be necessary.
· Acute central nervous system signs and symptoms may result from large ingestions of aspiration-induced hypoxia.
· After the initial episode,individuals should be followed for changes in blood variables and the delayed appearance of pulmonary oedema and chemical pneumonitis. Such patients should be followed for several days or weeks for delayed effects, including bone marrow toxicity, hepatic and renal impairment Individuals with chronic pulmonary disease will be more seriously impaired, and recovery from inhalation exposure may be complicated.
· Gastrointestinal symptoms are usually minor and pathological changes of the liver and kidneys are reported to be uncommon in acute intoxications.
· Chlorinated and non-chlorinated hydrocarbons may sensitize the heart to epinephrine and other circulating catecholamines so that arrhythmias may occur.Careful consideration of this potential adverse effect should precede administration of epinephrine or other cardiac stimulants and the selection of bronchodilators.
Treat symptomatically.

SECTION 5 Firefighting measures

Extinguishing media

SMALL FIRE:
‣ Water spray, dry chemical or CO2
LARGE FIRE:
‣ Water spray or fog.

Special hazards arising from the substance or mixture

Fire Incompatibility	‣ Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result

Advice for firefighters

Fire Fighting	‣ Alert Fire Brigade and tell them location and nature of hazard. ‣ May be violently or explosively reactive. ‣ Wear breathing apparatus plus protective gloves. ‣ Prevent, by any means available, spillage from entering drains or water course.
Fire/Explosion Hazard	‣ Liquid and vapour are highly flammable. ‣ Severe fire hazard when exposed to heat or flame. ‣ Vapour forms an explosive mixture with air. ‣ Severe explosion hazard, in the form of vapour, when exposed to flame or spark. Combustion products include: ‣ carbon monoxide (CO) ‣ carbon dioxide (CO2) silicon dioxide (SiO2) ‣ other pyrolysis products typical of burning organic material. **Contains low boiling substance:** Closed containers may rupture due to pressure buildup under fire conditions. **CARE**: Water in contact with hot liquid may cause foaming and a steam explosion with wide scattering of hot oil and possible severe burns. Foaming may cause overflow of containers and may result in possible fire.

SECTION 6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

Minor Spills	Environmental hazard - contain spillage. ‣ Clean up all spills immediately. ‣ Avoid breathing vapours and contact with skin and eyes. ‣ Wear protective clothing, impervious gloves and safety glasses. ‣ Shut off all possible sources of ignition and increase ventilation.
Major Spills	Environmental hazard - contain spillage. ‣ Silicone fluids, even in small quantities, may present a slip hazard. ‣ It may be necessary to rope off area and place warning signs around perimeter. ‣ Clean up area from spill, with suitable absorbant, as soon as practically possible. ‣ Final cleaning may require use of steam, solvents or detergents. ‣ Clear area of personnel and move upwind. ‣ Alert Fire Brigade and tell them location and nature of hazard. ‣ May be violently or explosively reactive. ‣ Wear breathing apparatus plus protective gloves. ‣ Clear area of all unprotected personnel and move upwind. ‣ Alert Emergency Authority and advise them of the location and nature of hazard. ‣ May be violently or explosively reactive. ‣ Wear full body clothing with breathing apparatus.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 Handling and storage

Precautions for safe handling

Safe handling	‣ **DO NOT** allow clothing wet with material to stay in contact with skin ‣ Avoid skin contact, including inhalation. ‣ Wear protective clothing when risk of exposure occurs. ‣ Use in a well-ventilated area. ‣ Prevent concentration in hollows and sumps.
Other information	‣ Store below 38 deg. C. ‣ Keep dry to avoid corrosion of cans. Corrosion may result in container perforation and internal pressure may eject contents of can ‣ Store in original containers in approved flammable liquid storage area. ‣ **DO NOT** store in pits, depressions, basements or areas where vapours may be trapped. ‣ No smoking, naked lights, heat or ignition sources. ‣ Keep containers securely sealed.

Conditions for safe storage, including any incompatibilities

Suitable container	Steel aerosol can ‣ Aerosol dispenser. ‣ Check that containers are clearly labelled.
Storage incompatibility	‣ Avoid reaction with oxidising agents

SECTION 8 Exposure controls / personal protection

Control parameters

Occupational Exposure Limits (OEL)

INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
New Zealand Workplace Exposure Standards (WES)	hydrocarbon propellant	LPG (Liquefied petroleum gas)	1000 ppm / 1800 mg/m3	Not Available	Not Available	Not Available

Exposure controls

Appropriate engineering controls	Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.

	The basic types of engineering controls are: Process controls which involve changing the way a job activity or process is done to reduce the risk. Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment.
Individual protection measures, such as personal protective equipment	
Eye and face protection	‣ Safety glasses with side shields. ‣ Chemical goggles.[AS/NZS 1337.1, EN166 or national equivalent] ‣ Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. ‣ No special equipment for minor exposure i.e. when handling small quantities. ‣ OTHERWISE: For potentially moderate or heavy exposures: ‣ Safety glasses with side shields. ‣ NOTE: Contact lenses pose a special hazard; soft lenses may absorb irritants and ALL lenses concentrate them. ‣ Close fitting gas tight goggles **DO NOT** wear contact lenses. ‣ Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lens or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available.
Skin protection	See Hand protection below
Hands/feet protection	‣ No special equipment needed when handling small quantities. ‣ OTHERWISE: ‣ For potentially moderate exposures: ‣ Wear general protective gloves, eg. light weight rubber gloves. ‣ For potentially heavy exposures: ‣ Wear chemical protective gloves, eg. PVC. and safety footwear.
Body protection	See Other protection below
Other protection	No special equipment needed when handling small quantities. **OTHERWISE:** ‣ Overalls. ‣ Skin cleansing cream. ‣ Eyewash unit. ‣ The clothing worn by process operators insulated from earth may develop static charges far higher (up to 100 times) than the minimum ignition energies for various flammable gas-air mixtures. This holds true for a wide range of clothing materials including cotton. ‣ Avoid dangerous levels of charge by ensuring a low resistivity of the surface material worn outermost. BRETHERICK: Handbook of Reactive Chemical Hazards.

Respiratory protection

Type AX-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Where the concentration of gas/particulates in the breathing zone, approaches or exceeds the "Exposure Standard" (or ES), respiratory protection is required. Degree of protection varies with both face-piece and Class of filter; the nature of protection varies with Type of filter.

Required Minimum Protection Factor	Half-Face Respirator	Full-Face Respirator	Powered Air Respirator
up to 5 x ES	Air-line*	AX-2 P2	AX-PAPR-2 P2 ^
up to 10 x ES	-	AX-3 P2	-
10+ x ES	-	Air-line**	-

* - Continuous Flow; ** - Continuous-flow or positive pressure demand
^ - Full-face
A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

- Cartridge respirators should never be used for emergency ingress or in areas of unknown vapour concentrations or oxygen content.
- The wearer must be warned to leave the contaminated area immediately on detecting any odours through the respirator. The odour may indicate that the mask is not functioning properly, that the vapour concentration is too high, or that the mask is not properly fitted. Because of these limitations, only restricted use of cartridge respirators is considered appropriate.
- Cartridge performance is affected by humidity. Cartridges should be changed after 2 hr of continuous use unless it is determined that the humidity is less than 75%, in which case, cartridges can be used for 4 hr. Used cartridges should be discarded daily, regardless of the length of time used

Aerosols, in common with most vapours/ mists, should never be used in confined spaces without adequate ventilation. Aerosols, containing agents designed to enhance or mask smell, have triggered allergic reactions in predisposed individuals.

SECTION 9 Physical and chemical properties

Information on basic physical and chemical properties

Appearance	Clear highly flammable liquid with no odour; does not mix with water.

Physical state	Liquid	**Relative density (Water = 1)**	0.7
Odour	Not Available	**Partition coefficient n-octanol / water**	Not Available
Odour threshold	Not Available	**Auto-ignition temperature (°C)**	Not Available
pH (as supplied)	Not Applicable	**Decomposition temperature (°C)**	Not Available
Melting point / freezing point (°C)	Not Available	**Viscosity (mm2/s)**	Not Applicable
Initial boiling point and boiling range (°C)	80	**Molecular weight (g/mol)**	Not Applicable
Flash point (°C)	<0	**Taste**	Not Available
Evaporation rate	Not Available	**Explosive properties**	Not Available
Flammability	HIGHLY FLAMMABLE.	**Oxidising properties**	Not Available
Upper Explosive Limit (%)	7.4	**Surface Tension (dyn/cm or mN/m)**	Not Available
Lower Explosive Limit (%)	1.2	**Volatile Component (%vol)**	Not Available
Vapour pressure (kPa)	Not Available	**Gas group**	Not Available
Solubility in water	Immiscible	**pH as a solution (1%)**	Not Applicable
Vapour density (Air = 1)	Not Available	**VOC g/L**	Not Available
Heat of Combustion (kJ/g)	Not Available	**Ignition Distance (cm)**	Not Available
Flame Height (cm)	Not Available	**Flame Duration (s)**	Not Available
Enclosed Space Ignition Time Equivalent (s/m3)	Not Available	**Enclosed Space Ignition Deflagration Density (g/m3)**	Not Available

SECTION 10 Stability and reactivity

Reactivity	See section 7
Chemical stability	‣ Silicone fluids are stable under normal storage conditions. ‣ Hazardous polymerisation will not occur. ‣ At temperatures > 150 C, silicones can slowly react with the oxygen in air. ‣ When heated > 300 C, silicones can slowly depolymerise to volatile siloxanes whether or not air is present. ‣ Elevated temperatures. ‣ Presence of open flame. ‣ Product is considered stable. ‣ Hazardous polymerisation will not occur.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 Toxicological information

Information on toxicological effects

a) Acute Toxicity	Based on available data, the classification criteria are not met.
b) Skin Irritation/Corrosion	There is sufficient evidence to classify this material as skin corrosive or irritating.
c) Serious Eye Damage/Irritation	Based on available data, the classification criteria are not met.
d) Respiratory or Skin sensitisation	Based on available data, the classification criteria are not met.
e) Mutagenicity	Based on available data, the classification criteria are not met.
f) Carcinogenicity	Based on available data, the classification criteria are not met.
g) Reproductivity	Based on available data, the classification criteria are not met.
h) STOT - Single Exposure	There is sufficient evidence to classify this material as toxic to specific organs through single exposure
i) STOT - Repeated Exposure	Based on available data, the classification criteria are not met.

j) Aspiration Hazard	Based on available data, the classification criteria are not met.

Inhaled	Inhalation of vapours may cause drowsiness and dizziness. This may be accompanied by sleepiness, reduced alertness, loss of reflexes, lack of co-ordination, and vertigo. Inhalation of aerosols (mists, fumes), generated by the material during the course of normal handling, may be damaging to the health of the individual. There is some evidence to suggest that the material can cause respiratory irritation in some persons. The body's response to such irritation can cause further lung damage. Material is highly volatile and may quickly form a concentrated atmosphere in confined or unventilated areas. The vapour may displace and replace air in breathing zone, acting as a simple asphyxiant. This may happen with little warning of overexposure. Inhalation of high concentrations of gas/vapour causes lung irritation with coughing and nausea, central nervous depression with headache and dizziness, slowing of reflexes, fatigue and inco-ordination. Central nervous system (CNS) depression may include general discomfort, symptoms of giddiness, headache, dizziness, nausea, anaesthetic effects, slowed reaction time, slurred speech and may progress to unconsciousness. Serious poisonings may result in respiratory depression and may be fatal. **WARNING**:Intentional misuse by concentrating/inhaling contents may be lethal.
Ingestion	Accidental ingestion of the material may be damaging to the health of the individual. Not normally a hazard due to physical form of product. Considered an unlikely route of entry in commercial/industrial environments
Skin Contact	This material can cause inflammation of the skin on contact in some persons. The material may accentuate any pre-existing dermatitis condition Spray mist may produce discomfort Open cuts, abraded or irritated skin should not be exposed to this material Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.
Eye	There is some evidence to suggest that this material can cause eye irritation and damage in some persons.
Chronic	Prolonged or repeated skin contact may cause drying with cracking, irritation and possible dermatitis following. Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure. Constant or exposure over long periods to mixed hydrocarbons may produce stupor with dizziness, weakness and visual disturbance, weight loss and anaemia, and reduced liver and kidney function. Skin exposure may result in drying and cracking and redness of the skin. **WARNING**: Aerosol containers may present pressure related hazards. Chronic solvent inhalation exposures may result in nervous system impairment and liver and blood changes. [PATTYS]

808 Silicone Spray	**TOXICITY**	**IRRITATION**
	Not Available	Not Available
naphtha petroleum, light, hydrotreated	**TOXICITY**	**IRRITATION**
	dermal (rat) LD50: 3.35 mg/kg[2]	Eye: no adverse effect observed (not irritating)[1]
	Inhalation (Rat) LC50: 0.26 mg/L4h[2]	Skin: adverse effect observed (irritating)[1]
	Oral (Rat) LD50: 16.75 mg/kg[2]	
polydimethylsiloxane	**TOXICITY**	**IRRITATION**
	Dermal (rabbit) LD50: >3000 mg/kg[2]	Eye (Rodent - rabbit): 100mg/1H - Mild
	Oral (Rat) LD50: >35000 mg/kg[2]	Eye (Rodent - rabbit): 100uL/24H - Mild
		Eye (Rodent - rabbit): 100uL/24H - Moderate
		Skin (Rodent - rabbit): 500uL/24H - Mild
hydrocarbon propellant	**TOXICITY**	**IRRITATION**
	Inhalation (Rat) LC50: 658 mg/l4h[2]	Eye: no adverse effect observed (not irritating)[1]
		Skin: no adverse effect observed (not irritating)[1]

Legend:	***1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2. Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances***

NAPHTHA PETROLEUM, LIGHT, HYDROTREATED	DHC Solvent Chemie (for EC No.: 926-605-8) Most Low Boiling Point Naphthas (LBPNs) have low actute toxicity to oral, dermal and inhalation routes of exposure, and mild to moderate skin and eye irritating effects. However, some heavier 'cracked' LBPNs (LKBPNs with greater olefinic content) have been found to be more irritating to the skin and eyes compared to non-cracked LBPNs. LBPNs are not known to be sensitising to the skin. Animal studies examined the effects of short-term and longer-term exposure to LBPNs through inhalation or oral routes. In male rats specifically, exposure to LBPNs resulted in kidney-related issues like increased kidney weight, kidney lesions, and hyaline droplet formation. However, the same effects were not seen in female rats, mice, or humans due to a mechanism of action involving a particular enzyme only found in male rats.

	Animal studies indicate that normal, branched and cyclic paraffins are absorbed from the gastrointestinal tract and that the absorption of n-paraffins is inversely proportional to the carbon chain length, with little absorption above C30. With respect to the carbon chain lengths likely to be present in mineral oil, n-paraffins may be absorbed to a greater extent than iso- or cyclo-paraffins. The major classes of hydrocarbons are well absorbed into the gastrointestinal tract in various species. In many cases, the hydrophobic hydrocarbons are ingested in association with fats in the diet. Some hydrocarbons may appear unchanged as in the lipoprotein particles in the gut lymph, but most hydrocarbons partly separate from fats and undergo metabolism in the gut cell. The High Benzene Naphthas (HBNs) contain mainly benzene but its adverse health effect is more with other components, which may cause adverse health effects involving a variety of organs. They may produce genetic damage as well as effects on reproduction and the unborn baby (generally at levels toxic to the mother). They may also cause cancers. Petroleum contains aromatic (benzene, toluene, ethyl benzene, napthalene) and aliphatic hydrocarbons (n-hexane), which can result in many detrimental health effects, including, cancer, tumour formation, hearing loss, and nervous system toxicity. Animal testing shows breathing in petroleum causes tumours of the liver and kidney; these are however not considered to be relevant in humans. Similarly, exposure to gasoline over a lifetime can cause kidney cancer in animals, but the relevance in humans is questionable. Most studies involving gasoline have shown that gasoline does not cause genetic mutation, including all recent studies in living human subjects (such as in petrol service station attendants). Animal studies show concentrations of toluene (>0.1%) can cause developmental effects such as lower birth weight and developmental toxicity to the nervous system of the foetus. Other studies show no adverse effects on the foetus. Prolonged contact with petroleum may result in skin inflammation and make the skin more sensitive to irritation and penetration by other materials.
POLYDIMETHYLSILOXANE	No toxic response noted during 90 day subchronic inhalation toxicity studies The no observable effect level is 450 mg/m3. Non-irritating and non-sensitising in human patch test. [Xerox]* Siloxanes may impair liver and hormonal function, as well as the lung and kidney. They have not been found to be irritating to the skin and eyes. They may potentially cause cancer (tumours of the womb in females) and may cause impaired fertility or infertility. The material may be irritating to the eye, with prolonged contact causing inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.
HYDROCARBON PROPELLANT	No significant acute toxicological data identified in literature search. inhalation of the gas

Acute Toxicity	✗	**Carcinogenicity**	✗
Skin Irritation/Corrosion	✓	**Reproductivity**	✗
Serious Eye Damage/Irritation	✗	**STOT - Single Exposure**	✓
Respiratory or Skin sensitisation	✗	**STOT - Repeated Exposure**	✗
Mutagenicity	✗	**Aspiration Hazard**	✗

Legend: ✗ ***– Data either not available or does not fill the criteria for classification***
✓ ***– Data available to make classification***

SECTION 12 Ecological information

Toxicity

808 Silicone Spray

Endpoint	Test Duration (hr)	Species	Value	Source
Not Available	Not Available	Not Available	Not Available	Not Available

naphtha petroleum, light, hydrotreated

Endpoint	Test Duration (hr)	Species	Value	Source
EC50	48h	Crustacea	0.64mg/l	2
EC50	96h	Algae or other aquatic plants	64mg/l	2
NOEC(ECx)	504h	Crustacea	0.17mg/l	2
LC50	96h	Fish	0.11mg/l	2

polydimethylsiloxane

Endpoint	Test Duration (hr)	Species	Value	Source
Not Available	Not Available	Not Available	Not Available	Not Available

hydrocarbon propellant

Endpoint	Test Duration (hr)	Species	Value	Source
EC50	96h	Algae or other aquatic plants	7.71mg/l	2
EC50(ECx)	96h	Algae or other aquatic plants	7.71mg/l	2
LC50	96h	Fish	24.11mg/l	2

Legend: ***Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 3. US EPA, Ecotox database - Aquatic Toxicity Data 4. ECETOC Aquatic Hazard Assessment Data 5. NITE (Japan) - Bioconcentration Data 6. METI (Japan) - Bioconcentration Data 7. Vendor Data 8. User defined data***

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
DO NOT discharge into sewer or waterways.

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
	No Data available for all ingredients	No Data available for all ingredients

Bioaccumulative potential

Ingredient	Bioaccumulation
hydrocarbon propellant	LOW (LogKOW = 3.39)

Mobility in soil

Ingredient	Mobility
	No Data available for all ingredients

SECTION 13 Disposal considerations

Waste treatment methods

Product / Packaging disposal	‣ **DO NOT** allow wash water from cleaning or process equipment to enter drains. ‣ It may be necessary to collect all wash water for treatment before disposal. ‣ In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first. ‣ Where in doubt contact the responsible authority. ‣ Consult State Land Waste Management Authority for disposal. ‣ Discharge contents of damaged aerosol cans at an approved site. ‣ Allow small quantities to evaporate. ‣ **DO NOT** incinerate or puncture aerosol cans.

Ensure that the hazardous substance is disposed in accordance with the Hazardous Substances (Disposal) Notice 2017

Disposal Requirements

Packages that have been in direct contact with the hazardous substance must be only disposed if the hazardous substance was appropriately removed and cleaned out from the package. The package must be disposed according to the manufacturer's directions taking into account the material it is made of. Packages which hazardous content have been appropriately treated and removed may be recycled.
The hazardous substance must only be disposed if it has been treated by a method that changed the characteristics or composition of the substance and it is no longer hazardous.

SECTION 14 Transport information

Labels Required

	
Marine Pollutant	
HAZCHEM	Not Applicable

Land transport (UN)

14.1. **UN number or ID number**	1950
14.2. **UN proper shipping name**	AEROSOLS
14.3. **Transport hazard class(es)**	Class: 2.1 Subsidiary Hazard: Not Applicable
14.4. **Packing group**	Not Applicable
14.5. **Environmental hazard**	Environmentally hazardous
14.6. **Special precautions for user**	Special provisions: 63; 190; 277; 327; 344; 381

	Limited quantity	1000ml

Air transport (ICAO-IATA / DGR)

14.1. **UN number**	1950
14.2. **UN proper shipping name**	Aerosols, flammable (engine starting fluid)
14.3. **Transport hazard class(es)**	ICAO/IATA Class: 2.1 ICAO / IATA Subsidiary Hazard: Not Applicable ERG Code: 10L
14.4. **Packing group**	Not Applicable
14.5. **Environmental hazard**	Environmentally hazardous
14.6. **Special precautions for user**	Special provisions: A1 A145 A167 A802 Cargo Only Packing Instructions: 203 Cargo Only Maximum Qty / Pack: 150 kg Passenger and Cargo Packing Instructions: Forbidden Passenger and Cargo Maximum Qty / Pack: Forbidden Passenger and Cargo Limited Quantity Packing Instructions: Forbidden Passenger and Cargo Limited Maximum Qty / Pack: Forbidden

Sea transport (IMDG-Code / GGVSee)

14.1. **UN number**	1950
14.2. **UN proper shipping name**	AEROSOLS
14.3. **Transport hazard class(es)**	IMDG Class: 2.1 IMDG Subsidiary Hazard: Not Applicable
14.4. **Packing group**	Not Applicable
14.5 **Environmental hazard**	Marine Pollutant
14.6. **Special precautions for user**	EMS Number: F-D, S-U Special provisions: 63 190 277 327 344 381 959 Limited Quantities: 1000 ml

14.7. Maritime transport in bulk according to IMO instruments

14.7.1. Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

14.7.2. Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Product name	Group
naphtha petroleum, light, hydrotreated	Not Applicable
polydimethylsiloxane	Not Applicable
hydrocarbon propellant	Not Applicable

14.7.3. Transport in bulk in accordance with the IGC Code

Product name	Ship Type
naphtha petroleum, light, hydrotreated	Not Applicable
polydimethylsiloxane	Not Applicable
hydrocarbon propellant	Not Applicable

SECTION 15 Regulatory information

Safety, health and environmental regulations / legislation specific for the substance or mixture

This substance is to be managed using the conditions specified in an applicable Group Standard

HSR Number	Group Standard
HSR002515	Aerosols Flammable Group Standard 2020

Please refer to Section 8 of the SDS for any applicable tolerable exposure limit or Section 12 for environmental exposure limit.

naphtha petroleum, light, hydrotreated is found on the following regulatory lists

Chemical Footprint Project - Chemicals of High Concern List
New Zealand Inventory of Chemicals (NZIoC)
New Zealand Land Transport Rule; Dangerous Goods 2005 - Schedule 2 Dangerous Goods in Limited Quantities and Consumer Commodities

polydimethylsiloxane is found on the following regulatory lists

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals
New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals - Classification Data
New Zealand Inventory of Chemicals (NZIoC)

hydrocarbon propellant is found on the following regulatory lists

Chemical Footprint Project - Chemicals of High Concern List
New Zealand Approved Hazardous Substances with controls
New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals
New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals - Classification Data
New Zealand Inventory of Chemicals (NZIoC)
New Zealand Workplace Exposure Standards (WES)

Additional Regulatory Information

Not Applicable

Hazardous Substance Location

Subject to the Health and Safety at Work (Hazardous Substances) Regulations 2017.

Hazard Class	Quantity (Closed Containers)	Quantity (Open Containers)
2.1.2A	3 000 L (aggregate water capacity)	3 000 L (aggregate water capacity)

Certified Handler

Subject to Part 4 of the Health and Safety at Work (Hazardous Substances) Regulations 2017.

Class of substance	Quantities
Not Applicable	Not Applicable

Refer Group Standards for further information

Maximum quantities of certain hazardous substances permitted on passenger service vehicles

Subject to Regulation 13.14 of the Health and Safety at Work (Hazardous Substances) Regulations 2017.

Hazard Class	Gas (aggregate water capacity in mL)	Liquid (L)	Solid (kg)	Maximum quantity per package for each classification
2.1.2A				1L (aggregate water capacity)

Tracking Requirements

Not Applicable

National Inventory Status

National Inventory	Status
Australia - AIIC / Australia Non-Industrial Use	Yes
Canada - DSL	Yes
Canada - NDSL	No (naphtha petroleum, light, hydrotreated; polydimethylsiloxane; hydrocarbon propellant)
China - IECSC	Yes
Europe - EINEC / ELINCS / NLP	No (polydimethylsiloxane)
Japan - ENCS	No (naphtha petroleum, light, hydrotreated)

National Inventory	Status
Korea - KECI	Yes
New Zealand - NZIoC	Yes
Philippines - PICCS	Yes
USA - TSCA	All chemical substances in this product have been designated as TSCA Inventory ‘Active'
Taiwan - TCSI	Yes
Mexico - INSQ	Yes
Vietnam - NCI	Yes
Russia - FBEPH	Yes
UAE - Control List (Banned/Restricted Substances)	No (naphtha petroleum, light, hydrotreated; polydimethylsiloxane; hydrocarbon propellant)
Legend:	***Yes = All CAS declared ingredients are on the inventory*** ***No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration.***

SECTION 16 Other information

Revision Date	05/07/2023
Initial Date	05/07/2023

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

Definitions and abbreviations

- PC—TWA: Permissible Concentration-Time Weighted Average
- PC—STEL: Permissible Concentration-Short Term Exposure Limit
- IARC: International Agency for Research on Cancer
- ACGIH: American Conference of Governmental Industrial Hygienists
- STEL: Short Term Exposure Limit
- TEEL: Temporary Emergency Exposure Limit。
- IDLH: Immediately Dangerous to Life or Health Concentrations
- ES: Exposure Standard
- OSF: Odour Safety Factor
- NOAEL: No Observed Adverse Effect Level
- LOAEL: Lowest Observed Adverse Effect Level
- TLV: Threshold Limit Value
- LOD: Limit Of Detection
- OTV: Odour Threshold Value
- BCF: BioConcentration Factors
- BEI: Biological Exposure Index
- DNEL: Derived No-Effect Level
- PNEC: Predicted no-effect concentration
- MARPOL: International Convention for the Prevention of Pollution from Ships
- IMSBC: International Maritime Solid Bulk Cargoes Code
- IGC: International Gas Carrier Code
- IBC: International Bulk Chemical Code

- AIIC: Australian Inventory of Industrial Chemicals
- DSL: Domestic Substances List
- NDSL: Non-Domestic Substances List
- IECSC: Inventory of Existing Chemical Substance in China
- EINECS: European INventory of Existing Commercial chemical Substances
- ELINCS: European List of Notified Chemical Substances
- NLP: No-Longer Polymers
- ENCS: Existing and New Chemical Substances Inventory
- KECI: Korea Existing Chemicals Inventory
- NZIoC: New Zealand Inventory of Chemicals
- PICCS: Philippine Inventory of Chemicals and Chemical Substances
- TSCA: Toxic Substances Control Act
- TCSI: Taiwan Chemical Substance Inventory
- INSQ: Inventario Nacional de Sustancias Químicas
- NCI: National Chemical Inventory

- FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances

This document is copyright.
Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH.
TEL (+61 3) 9572 4700.

Disclaimer: This SDS was prepared by a third party for product identification purposes only and is not endorsed by or affiliated with the original brand owner.